


Name: P. NOUHEN  
Visa: 

Name: M.NARCHE  
Visa: 



EDITING	APPROVAL	INDEX	DATE
---------	----------	-------	------

Converters	Cables	Sensors	Diameter	Fluid Temperature	Note		
Time Delta C model FSV	FLY8 ___ 1	FLW1 0 2-Y	50-400mm	-40 to 80°C	Standart type		
		FLW4 0 2-Y	200-1200mm				
		FLW5 0 2-Y	200-6000mm				
	Included with sensor	FLY30 ___ 1	FLW1 1 2-Y	50-400mm	-40 to 80°C	Submerged type	
			FLW4 1 2-Y	200-1200mm			
			FLW5 1 2-Y	200-6000mm			
	FLY9 ___ 1	FLSE12 2	25-100mm	0 to 120°C	50-225mm (100°C max.) Small Diameter		
		FLSE22 2	50-150mm	0 to 120°C			
		FLD220S1-Y	13-100mm	-40 to 100°C			
	Time Delta S model FLV <i>(Production is stopped except Ex version)</i>	FLY1 ___ 1	FLW1 0 2-Y	50-400mm	-40 to 80°C	Standart type	
FLW4 0 2-Y			200-1200mm				
FLW5 0 2-Y			200-6000mm				
Included with sensor		FLY2 ___ 1	FLW1 1 2-Y	50-400mm	-40 to 80°C	Submerged type	
			FLW4 1 2-Y	200-1200mm			
			FLW5 1 2-Y	200-6000mm			
FLY2 ___ 1		FLW1 2 2-Y	50-400mm	-40 to 80°C	Ex type		
		FLW4 2 2-Y	200-1200mm				
		FLW5 2 2-Y	200-6000mm				
FLY2 ___ 1		FLD220S1-Y	13-100mm	-40 to 100°C	Small Diameter High Temp. Application		
	FLD320S1-Y	50-400mm	-40 to 200°C				
	Time Delta H model FLH	FLY1 ___ 1	FLW1 0 2-Y	50-400mm		-40 to 80°C	Standart type
FLW4 0 2-Y			200-1200mm				
FLW5 0 2-Y			200-6000mm				
Included with sensor		FLY2 ___ 1	FLW1 1 2-Y	50-400mm	-40 to 80°C	Submerged type	
			FLW4 1 2-Y	200-1200mm			
			FLW5 1 2-Y	200-6000mm			
FLY2 ___ 1		FLD320S1-Y	50-400mm	-40 to 200°C	High Temp. Application		
		M-Flow model FLR <i>(Production is stopped)</i>	FLY30 ___ 1	FLSE12 2		25-100mm	-20 to 100°C
			FLY40 ___ 1	FLSE22 2		50-225mm	-20 to 80°C
FLSE31 2				50-300mm			
		FLSE41 2	300-600mm				

 Only for information or spare parts